

Package: geozoo (via r-universe)

September 18, 2026

Version 0.5.1

Date 2016-05-06

Title Zoo of Geometric Objects

Description Geometric objects defined in 'geozoo' can be simulated or displayed in the R package 'tourr'.

URL <http://schloerke.github.io/geozoo/>, <http://www.ggobi.org>,
<https://github.com/schloerke/geozoo>

BugReports <https://github.com/schloerke/geozoo/issues>

Depends R (>= 1.8.0)

Imports bitops, stats

Suggests tourr, roxygen2 (>= 5.0.0), testthat

License GPL-2

RoxygenNote 5.0.1

Repository <https://schloerke.r-universe.dev>

Date/Publication 2016-05-06 03:06:47 UTC

RemoteUrl <https://github.com/schloerke/geozoo>

RemoteRef HEAD

RemoteSha f633781f098779f8ad2b95c19811b11738b39068

Contents

boy.surface	2
conic.spiral	3
conic.spiral.nautilus	4
cross.cap	5
cross.polytope	5
cube.dotline	6
cube.face	7
cube.iterate	8
cube.solid.grid	8

cube.solid.random 9

dini.surface 10

ellipsoid 11

enneper.surface 12

f_composition 12

f_helmert 13

klein.fig.eight 14

mobius 15

mobius.experiment 15

print.geozoo 16

print.geozooNoScale 17

roman.surface 17

simplex 18

sphere.hollow 19

sphere.solid.grid 20

sphere.solid.random 20

torus 21

torus.flat 22

write.xml 23

Index 24

boy . surface	<i>Boy Surface</i>
---------------	--------------------

Description

A function to produce a Boy Surface.

Usage

```
boy.surface(n = 10000)
```

Arguments

n number of points

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/other/>

Examples

```
## Generates a Boy Surface
boy.surface(n = 1000)
```

conic.spiral	<i>Conic Spiral</i>
--------------	---------------------

Description

A function to produce a conic spiral

Usage

```
conic.spiral(n = 10000, a = 0.2, b = 1, c = 0.1, w = 2)
```

Arguments

n	number of points
a	final radius of cone
b	height of object
c	inner radius
w	number of spirals

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/other/>

Examples

```
## Generates a Conic Spiral  
conic.spiral(n = 1000)
```

conic.spiral.nautilus *Conic Spiral (Nautilus Shape)*

Description

A function to produce a Conic Spiral in a nautilus shape

Usage

```
conic.spiral.nautilus(n = 10000, a = 0.2, b = 0.1, c = 0, w = 2)
```

Arguments

n	number of points
a	final radius of cone
b	height of object
c	inner radius
w	number of spirals

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/other/>

Examples

```
## Generates a Nautilus Conic Spiral  
conic.spiral.nautilus( n = 1000 )
```

`cross.cap`*Cross Cap*

Description

A function to generate a cross cap

Usage

```
cross.cap(n = 10000)
```

Arguments

n	number of points
---	------------------

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/other/>

Examples

```
## Generates a Cross Cap  
cross.cap( n = 1000 )
```

`cross.polytope`*Cross Polytope*

Description

A function generate a cross polytope, cube dual, with vertices and a wire frame.

Usage

```
cross.polytope(p = 3)
```

Arguments

p	dimension of object
---	---------------------

Value

points	location of points
edges	edges of the object

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/cube/>

Examples

```
# Generates a 3-D Cross Polytope
cross.polytope(p = 3)
```

cube.dotline

Cube with points along the wire frame

Description

A function to generate a cube with points on its face

Usage

```
cube.dotline(p = 3)
```

Arguments

p	dimension of object
---	---------------------

Value

points	location of points
edges	edges of the object

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/cube/>

Examples

```
## Generates a cube with points along its wire frame
cube.dotline(p = 3)
```

cube.face	<i>Cube with points on the 'face'</i>
-----------	---------------------------------------

Description

A function to generate a cube with points on its face

Usage

```
cube.face(p = 3)
```

Arguments

p	dimension of object
---	---------------------

Value

points	location of points
edges	edges of the object

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/cube/>

Examples

```
## Generates a cube with points on its face
cube.face(p = 3)
```

`cube.iterate`*Cube*

Description

A function generate a cube with vertices and a wire frame

Usage

```
cube.iterate(p = 3)
```

Arguments

p	dimension of object
---	---------------------

Value

points	location of points
edges	edges of the object

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/cube/>

Examples

```
## Generates a cube  
cube.iterate(p = 3)
```

`cube.solid.grid`*Equidistant Solid Cube*

Description

A function to generate a solid cube with equidistant points

Usage

```
cube.solid.grid(p = 3, n = 8)
```

Arguments

p	dimension of object
n	length of number of points in each dimension

Value

points	location of points
edges	edges of the object

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/cube/>

Examples

```
## Generates a solid cube with equidistant points
cube.solid.grid(p = 3, n = 8)
```

cube.solid.random	<i>Solid Cube</i>
-------------------	-------------------

Description

A function to generate a solid cube with random points

Usage

```
cube.solid.random(p = 3, n = 850 * (2^p))
```

Arguments

p	dimension of object
n	number of points

Value

points	location of points
edges	edges of the object

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/cube/>

Examples

```
## Generates a solid cube with random points
cube.solid.random(p = 3, n = 1000)
```

dini.surface	<i>Dini Surface</i>
--------------	---------------------

Description

A function to generate a dini surface.

Usage

```
dini.surface(n = 10000, a = 1, b = 1)
```

Arguments

n	number of points
a	outer radius of object
b	space between loops

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/other/>

Examples

```
## Generates a Dini Surface
dini.surface(n = 1000, a = 1, b = 1)
```

ellipsoid	<i>Ellipsoid</i>
-----------	------------------

Description

A function to generate an ellipsoid

Usage

```
ellipsoid(n = 10000, a = 1, b = 1, c = 3)
```

Arguments

n	number of points
a	radius in x direction
b	radius in y direction
c	radius in z direction

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/other/>

Examples

```
## Generates an ellipsoid  
ellipsoid(n = 1000, a = 1, b = 1, c = 3)
```

enneper.surface	<i>Enneper's Surface</i>
-----------------	--------------------------

Description

A function to generate Enneper's surface

Usage

```
enneper.surface(n = 10000, a = 4)
```

Arguments

n	number of points
a	angle, radians, minimum and maximum. $-a < \text{angle} < a$

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/other/>

Examples

```
## Generates an Enneper Surface
enneper.surface(n = 1000, a = 4)
```

f_composition	<i>f_composition</i>
---------------	----------------------

Description

Function to take a d-dimensional compositional data set and transform it using a Helmert transformation into (p-1)-space, where it lives. Mostly internally used, but could be useful for setting up new compositional data.

Usage

```
f_composition(data)
```

Arguments

data	object
------	--------

Value

data	points in (d-1)-dimensional space
------	-----------------------------------

Author(s)

Di Cook

References

<http://schloerke.github.io/geozoo/simplices/>

f_helmert

f_helmert

Description

Function to set up a Helmert transformation of a (d-1)-dimensional shape in p-space down into its (p-1)-space. Mostly internally used, but could be useful for setting up new compositional data.

Usage

```
f_helmert(d)
```

Arguments

d	object
---	--------

Value

helmert	transformation matrix
---------	-----------------------

Author(s)

Di Cook

References

<http://schloerke.github.io/geozoo/simplices/>

klein.fig.eight	<i>Figure Eight Klein Bottle</i>
-----------------	----------------------------------

Description

A function to generate a figure eight Klein bottle

Usage

```
klein.fig.eight(n = 10000, a = 3, b = 1)
```

Arguments

n	number of points
a	radius of outer radius
b	radius of inner radius

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/other/>

Examples

```
## Generates a figure eight Klein bottle.  
klein.fig.eight(n = 1000, a = 3, b = 1)
```

`mobius`*Mobius*

Description

A function to generate a mobius strip in the third or fourth dimension.

Usage

```
mobius(p = 3, n = 10000)
```

Arguments

p	dimension of object. (3)
n	number of points

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/mobius/>

Examples

```
## Generates a mobius strip.  
mobius(3, n = 1000)
```

`mobius.experiment`*Mobius Experiment*

Description

A function to generate a 5-D mobius strip in the third dimension.

Usage

```
mobius.experiment(p = 5, n = 10000)
```

Arguments

p	dimension of object. (5)
n	number of points

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/mobius/>

Examples

```
## Generates a mobius strip.  
mobius.experiment(5, n = 1000)
```

print.geozoo

Print

Description

Prints geozoo objects with tourr or prints them

Usage

```
## S3 method for class 'geozoo'  
print(x, ...)
```

Arguments

x	geozoo object
...	other arguments

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/>

Examples

```
## Not run:  
example(boy.surface)  
example(cube.face)  
  
## End(Not run)
```

print.geozooNoScale *Print Without Rescale*

Description

Prints objects without rescaling them to 0, 1 in each dim

Usage

```
## S3 method for class 'geozooNoScale'  
print(x, ...)
```

Arguments

x	geozoo object
...	other arguments

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/>

Examples

```
## Not run:  
torus()  
  
## End(Not run)
```

roman.surface *Roman Surface*

Description

A function to generate a Roman surface, also known as a Steiner surface

Usage

```
roman.surface(n = 10000, a = 1)
```

Arguments

n	number of points
a	maximum radius of object

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/other/>

Examples

```
## Generates a Roman surface.  
roman.surface(n = 1000, a = 1)
```

simplex

Simplex

Description

A function to generate a simplex

Usage

```
simplex(p = 3)
```

Arguments

p	dimension of object
---	---------------------

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/simplices/>

Examples

```
## Generates a simplex  
simplex(p = 3)
```

sphere.hollow	<i>Sphere</i>
---------------	---------------

Description

A function to generate a sphere with points on the surface

Usage

```
sphere.hollow(p = 3, n = p * 500)
```

Arguments

p	dimension of object
n	number of points

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/sphere/>

Examples

```
## Generates a sphere with points on the surface  
sphere.hollow(p = 3, n = 1000)
```

sphere.solid.grid	<i>Solid Sphere with Equidistant Points</i>
-------------------	---

Description

A function to generate a solid sphere with equidistant points.

Usage

```
sphere.solid.grid(p = 3, n = 8)
```

Arguments

p	dimension of object
n	maximum number of points in the diameter

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/sphere/>

Examples

```
## Generates a solid sphere with equidistant points  
sphere.solid.grid(p = 3, n = 8)
```

sphere.solid.random	<i>Solid sphere with Random Points</i>
---------------------	--

Description

A function to generate a solid sphere with random points

Usage

```
sphere.solid.random(p = 3, n = p * 500)
```

Arguments

p	dimension of object
n	number of points

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/sphere/>

Examples

```
## Generates a solid sphere with random points.
sphere.solid.random(p = 3, n = 1000)
```

torus

Torus

Description

A function to generate a torus in any dimension

Usage

```
torus(p = 3, n = 10000, radius = 2^((p - 2):0))
```

Arguments

p	dimension of object
n	number of points
radius	radiuses of the torus, set from largest to smallest

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/torus/>

Examples

```
## Generates a torus
torus(p = 3, n = 1000)
```

torus.flat	<i>Flat Torus</i>
------------	-------------------

Description

A function to generate a flat torus in any dimension

Usage

```
torus.flat(p = 4, n = 10000)
```

Arguments

p	dimension of object (number of circles x2)
n	number of points

Value

points	location of points
edges	edges of the object (null)

Author(s)

Barret Schloerke

References

<http://schloerke.github.io/geozoo/mobius/torus/>

Examples

```
## Generates a Flat Torus
torus.flat(p = 4, n = 1000)
```

`write.xml`*Write XML File*

Description

A function that allows the user to write an object into an .xml.

Usage

```
write.xml(object.function, filepath, title)
```

Arguments

<code>object.function</code>	i.e. <code>cube()</code> or <code>sphere()</code>
<code>filepath</code>	where you would like to save the file in quotes
<code>title</code>	title of the file in quotes

Author(s)

Barret Schloerke

Index

* **dynamic**

- boy.surface, [2](#)
- conic.spiral, [3](#)
- conic.spiral.nautilus, [4](#)
- cross.cap, [5](#)
- cross.polytope, [5](#)
- cube.dottedline, [6](#)
- cube.face, [7](#)
- cube.iterate, [8](#)
- cube.solid.grid, [8](#)
- cube.solid.random, [9](#)
- dini.surface, [10](#)
- ellipsoid, [11](#)
- enneper.surface, [12](#)
- klein.fig.eight, [14](#)
- mobius, [15](#)
- mobius.experiment, [15](#)
- print.geozoo, [16](#)
- print.geozooNoScale, [17](#)
- roman.surface, [17](#)
- simplex, [18](#)
- sphere.hollow, [19](#)
- sphere.solid.grid, [20](#)
- sphere.solid.random, [20](#)
- torus, [21](#)
- torus.flat, [22](#)
- write.xml, [23](#)

- boy.surface, [2](#)

- conic.spiral, [3](#)
- conic.spiral.nautilus, [4](#)
- cross.cap, [5](#)
- cross.polytope, [5](#)
- cube.dottedline, [6](#)
- cube.face, [7](#)
- cube.iterate, [8](#)
- cube.solid.grid, [8](#)
- cube.solid.random, [9](#)

- dini.surface, [10](#)

- ellipsoid, [11](#)
- enneper.surface, [12](#)

- f_composition, [12](#)
- f_helmert, [13](#)

- klein.fig.eight, [14](#)

- mobius, [15](#)
- mobius.experiment, [15](#)

- print.geozoo, [16](#)
- print.geozooNoScale, [17](#)

- roman.surface, [17](#)

- simplex, [18](#)
- sphere.hollow, [19](#)
- sphere.solid.grid, [20](#)
- sphere.solid.random, [20](#)

- torus, [21](#)
- torus.flat, [22](#)

- write.xml, [23](#)